

DAMATRÀ

LOUNGE

Design: R&D Sitlosophy®



Available with an extra-large squared or shaped backrest, Damatra is a versatile armchair that adapts to any environment. There is a wide choice of bases – from the sled to the pyramid base, from the disc base to the aluminium spokes – which transform it from a perfect armchair for waiting areas into a modern seat for any lounge environment.

In. Fb. Ig.

1

SIT LOSOPHY®



Specifications

Structure Padding	Multilayer shell High-density, flexible polyurethane foam 3,5 cm thick, density 40 rc
Swivel base	B80 ø740 polished aluminum 4-star, optional: B81 black painted aluminum 4-star B68 ø700 4-Star polished aluminum, optional: B70 black painted aluminum 4-star on item 1523; 4-spokes pyramid ø840 on items1522B/1525B; Inox steel round flat ø470 on item 1524
Fixed base	Chrome cantilever base ø20x2 on version 1520



Components and/or modules

Image	Dimension		Cod.	Description	
	Н	73			
	L	70	C1520V	Chrome chair	
	Р	78			
	Н	80			
	L	70	C1521B	Swivel armchair, 4-star aluminum base	
	Р	74			
	Н	82			
	L	70	C1522B	Swivel armchair, 4-legged pyramid base ø840	
	Р	84			
	Н	82			
	L	68	C1523B	Swivel armchair, 4-star aluminum base	
	Р	70			
	Н	83			
	L	68	C1524V	Swivel armchair, ø470 stainless steel disc base	
	Р	48			
	Н	82			
Ţ	L	68	C1525B	Swivel armchair, 4-legged pyramid base ø840	
$ \land $	Р	84			

3



Coverings

Cat.	Covering		Description	Certifications	Folder Colors
2		Angel 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 1IM	Ø
2		One 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	OEKO-TEX @ ISIA CONTROL ISIA CONTROL <thisia control<="" th=""> ISIA CONTROL ISI</thisia>	Ø
2		Gazebo 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 1IM	Ø
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	Version of the state of the sta	Ø
3		Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 1IM	Ø
3		Mini 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	OEKO-TEX® STANDARD 100 Oracle control of the second se	Q
3		Chili 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	CEKO-TEX® STANDARD DISJAGCONTACT Weisheld with the contraction Weisheld with the contraction Weisheld with the contraction Trolocose Fire proof class 1IM	Ø
4		Leather 13 colors	100% genuine leather	Vera pelle	Ø
5		Step 15 colors	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	CEKO-TEX® CRANDARD INFORMATION CARACTERISTIC CONSTRUCTION	Q

In. Fb. Ig.

4



Cat.	Covering		Description	Certifications	Folder Colors
5		Go Check 15 colors	Weight: ± 310 g/sqm Composition: 100% Trevira CS Martindale: 80,000 cycles	Reverse Contraction of the second sec	Q
6		Panama leather 15 colors	Composition: 100% corrected grain leather Thickness: 1.0 – 1.2mm Flexural strength: 50,000 cycles	Vera pelle Flame resistance treatment available on request	œ
7		Grain 15 colors	Weight: ± 615 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles California TB 117-2013	OEKO-TEX® CONFIDENCE IN TEXTUES STANDARD 1000 1076-182 001 Tated for hermful substance, www.celen-tax.centriatacter/10	Q
7		Focus 15 colors	Weight: ± 660 g/sqm Composition: 100% New Zealand Wool Martindale: 100,000 cycles CLASS 1 IM - UNI 9175	CONTIGENCE IN TEXTUES CONTIGENCE IN TEXTUES STANDARD 100 1076-102 0TI Teated for harmfig staturosa, www.osto-tex.convistantese:100	Ś
7		Extrema 15 colors	Weight: ± 480 g/sqm Composition: 63% PU – 29% COT – 8% PES Martindale: 150,000 cycles Features: Antibacterial protection	Ultra-Fresh*	Ø

Certifications



00

ISO 1400









Ministerial Homologation Class 1IM on request. Search for FSC® products

https://www.sitlosophy.com/en/seat/damatra/



SIT LOSOPHY®

INSTRUCTIONS FOR USE AND MAINTENANCE

GENERAL INFORMATION

If the chair is used as a computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

MECHANISMS

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to prevent it from returning abruptly and accidentally forward.

Care instructions: It is recommended to clean the mechanism periodically to prevent dust or other indoor pollutants from affecting its operation or causing squeaking.

Warnings: All mechanism adjustments (height, sideshift, seat and backrest adjustment, swivel) must be operated while seated to avoid improperly straining the mechanism. When adjusting, be careful to avoid any risk of entrapment or crushing of the fingers.

PADDED PARTS

Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in

any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

UNPADDED PARTS

Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminium metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water; For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.