

HOLA

GUEST AND COMMUNITY CHAIRS

Design: S.I. DESIGN STUDIO





Hola is a reinterpretation of the classic waiting mesh back chair with clean and contemporary lines. Perfect match for executive and task armchairs, it is available with a black or chrome sled frame, in two variants with white or black mesh, and a comfortable padded seat.

Specifications

Seat	Multilayer
Backrest	Black polypropylene lined with black or white self-supporting mesh
Frame	Cantilever base ø22x1,5 chrome or black painted
Padding	Flexible polyurethane foam seat 3,5 cm thick, density 40 rc
Armrests	Structural,made of black polypropylene

1




Components and/or modules

Image	Dimension		Cod.	Description
	н	87		
	L	59	N1410V	Black cantilever stack armchair, mesh backrest, padded seat
	Ρ	59		
	Н	87	_	Chrome cantilever stack armchair, mesh backrest, padded seat
	L	59	C1410V	
A	Р	59		

Mesh

Composition: 70% polyvinyl -30% PES. Martindale : 100,000 cycles





Coverings

Cat.	Coverings		Description	Certifications	Folder Colors
1		Madrid 5 colors	Weight: ± 230 g/sqmComposition: 100% PP polypropylene F.R. Martindale: 80,000 cycles	EKO-TEX® STANDARD 100 Microsoft Contractor Microsoft Contractor	Ø
1		Cove 5 colors	Weight: ± 565 g/sqm Composition: 82% PVC – 7% Cotton – 11% Polyester Martindale: 50,000 cycles		Ø
2		Angel 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 11M	Ø
2		One 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	OEKO-TEX @ STATACTIVE OEKO-TEX @ STATACTIVE OEKO-TEX @ STATACTIVE With the state withe state with the state with the state withe state wit	Ø
2		Gazebo 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 1IM	Ø
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	CEKO-TEX® STANDARD 100 Orange enter one Wards to another the Wards to another the Transformer Fire proof class 1IM	Ø
3	11 Martin	Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 1IM	Ø
3		Mini 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	Records to the second s	Ø
3		Chili 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	CEKO-TEX® STANDARD BISSIG CONTROL Water Main Million Water Main Millio	Ø

In. Fb. Ig.

3



Cat.	Coverings		Description	Certifications	Folder Colors
5		tep 5 colors	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	VEKO-TEX® STANDARD TOO Provide the answer With the transmitter to The proof class 1IM	Ø
5		o Check 5 colors	Weight: ± 310 g/sqm Composition: 100% Trevira CS Martindale: 80,000 cycles	CECO-TEXO SUBJECTORY Market And Andrews With Andrews Fire proof class 1IM	Ø
7		rain 5 colors	Weight: ± 615 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles California TB 117-2013	OEKO-TEX® CONTIDENCE IN TEATLES STANDARD 100 107-182 01 Tatel of herrol (abdatases, www.gelio-te.com/standard100	Ø
7		ocus 5 colors	Weight: ± 660 g/sqm Composition: 100% New Zealand Wool Martindale: 100,000 cycles CLASS 1 IM - UNI 9175	CONTIDENCE IN TEXTUS ECOLOGIC WWW.acchablel.eu	Ø
7	TO THE REPORT OF THE PARTY OF T	xtrema 5 colors	Weight: ± 480 g/sqm Composition: 63% PU – 29% COT – 8% PES Martindale: 150,000 cycles Features: Antibacterial protection	Ultra-Fresh* Fire proof class 11M	Q

Certifications











10000

Search FSC® products



4

SIT LOSOPHY®

INSTRUCTIONS FOR USE AND MAINTENANCE

GENERAL INFORMATION

If the chair is used as a computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

PADDED PARTS

Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

UNPADDED PARTS

Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water: For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.

In. Fb. lg.