

# HOST

### CHAIRS AND TUB CHAIRS

Design: R&D Sitlosophy®



Wild card of the collection, Host is an armchair that fits perfectly into the most diverse environments, from the home to the office, from the waiting room to the restaurant thanks to its contemporary and minimalist lines. The new versions with 4-legged or sled metal structure, painted in attractive and trendy colours, can be matched with the colour of the upholstery to obtain an elegant monochromatic look or mixed with a contrasting nuance for a more eclectic result.

#### Specifications

Structure	Multilayer			
Padding	Flexible polyurethane foam 2 / 3 cm thick, density 40 rc			
Armrests	Multilayer			
Height adjustment	Gas pump (UNI 9084 certified) on items 1654-1656			
Castors	AR4 Polyamide Ø 65 on item 1654 AR8 Polyamide Ø 50 on item 1652			
Swivel base	B70 4-spoke black painted aluminium on item N1650; B68 4-spoke polished aluminium on items C1650- C1656; B63 black nylon on item 1654 ; 4-spoke black nylon pyramid base on items 1651-1652; 4-spoke polished cast-aluminum pyramid base on item 1653.			
Fixed base	<ul> <li>Steel wire cantilever base ø11 painted in: charcoal, white, powder pink,sage green on item 1658.</li> <li>4-Legged steel tube base ø18x1,5 painted in: charcoal, white, powder pink, sage green on item 1659.</li> <li>4-legged natural ashwood base on item 1655.</li> <li>4-Legs chrome steel tube base ø16x2 on item 1657</li> </ul>			

### In. Fb. Ig.



#### Components and/or modules

Image	Dimensi	on	Cod.	Description	
	Н	80			
	L	60	N1650B	Swivel armchair, 4-star black aluminum base	
	Р	70			
	Н	82			
	L	60	N1654G	Swivel armchair, height adjustable, nylon base on castors	
	Р	64			
	Н	82			
	L	60	N1651B	Swivel armchair, black 4-spoke pyramid nylon base	
7117	Р	67			
	Н	82			
	L	60	N1652B	Swivel armchair, black 4-spoke pyramid nylon base on castors	
	Р	67			
	н	80			
	L	60	C1650B	Swivel armchair, 4-star polished aluminum base	
The second	Ρ	70			
	Н	81			
	L	60	C1653B	Swivel armchair, 4-star pyramid aluminum base	
	Ρ	72			
	Н	82			
	L	60	AT1658V	Charcoal painted cantilever armchair	
	Р	58			

In. Fb. Ig.

## SIT LOSOPHY®

Image	Dimensio	n	Cod.	Description	
	н	82		White painted cantilever armchair	
ATT	L	60	B1658V		
	Р	58			
	н	82			
	L	60	CP1658V	Pink powder painted cantilever armchair	
	Р	58			
	н	82			
	L	60	VR1658V	Sage green painted cantilever armchair	
	Ρ	58			
	н	82		Guest chair, charcoal painted 4-legged base	
$(\Pi)$	L	60	AT1659V		
	Ρ	60			
	Н	82			
	L	60	B1659V	Guest chair, white painted 4-legged base	
$I \downarrow I \downarrow$	Р	60			
	Н	82			
(Th	L	60	CP1659V	Guest chair, pink powder painted 4-legged base	
[ ][ ]	Р	60			
	Н	82			
(Th	L	60	VR1659V	Guest chair, sage green painted 4-legged base	
1 1	Р	60			

In. Fb. Ig.

## **SIT** LOSOPHY®

Image	Dimension		Cod.	Description	
	Н	79			
	L	60	W-N1655V	Armchair, 4-legged solid ash wood base, natural finish	
/	Р	55			
	Н	89-113		Swivel high chair, gas lift, 4-star aluminum base	
T	L	60	C1656G		
	Р	70			
	Н	113	C1657V	High chair, 4-legged chrome base	
	L	60			
	Р	55			

#### Metal





#### Coverings

Cat.	Covering		Description	Certifications	Folder Colors
2		<b>Angel</b> 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 1IM	Ø
2		<b>One</b> 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	OEKO-TEX @ STADACKINGOT         OEKO-TEX @ STADACKINGOT         OEKO-TEX @ STADACKINGOT           British and an antikar water Water back water water State of a state water water Water back water water water Fire proof class 1IM	Ø
2		<b>Gazebo</b> 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 1IM	Ø
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	VEKO-TEX® STANDARDING USUASCONTROOT Weins and	Ø
3		Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 1IM	Ø
3		Mini 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	OEKO-TEX®           STANDARD 100           Draw of an open of the stand of an open open of the stand of an open of the stand of an open of the stan	Q
3		<b>Chili</b> 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	VEKO-TEX® STADARTICO USUBACHTOO Water with the stand Water with the standard Water with the standard W	Ø
4		Leather 13 colors	100% genuine leather	Vera pelle	Q



Cat.	Covering	Description	Certifications	Folder Colors
5	<b>Step</b> 15 cd	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	CEKO-TEX® STANDARD 100 Parade common Will be the standard and Will be the standard and Will be the standard and Fire proof class 1IM	Ø
5	<b>Go C</b> 15 cc		OEKO-TEXO Sintenence With an antiversity         Image: Constant Distant           Image: Constant         Image: Constant           Image: Constant         Image: Constant	Ø
6	Pana leath 15 ce	er Thickness: 10 – 12 mm	Flame resistance treatment available on request	Ø
7	<b>Grair</b> 15 cd		OEKO-TEX ® CONTIDENCE IN TEXTILES STANDARD 1070-102 OT Tasted for harmful abatanos, www.oklowite.com/sandter!10	Ø
7	<b>Focu</b> 15 со	Wool	CONTIDENCE IN TEXTLES CONTIDENCE IN TEXTLES STANDARD 100 1076-182 UT Tested to framel adultros, www.celoi-tex.convisitedser100	Ø
7	Extre 15 cc	63% PU – 29% COT – 8% PES	Ultra-Fresh* Fire proof class 1IM	Ø

#### Certifications



https://www.sitlosophy.com/en/seat/host-stool/

## SIT LOSOPHY®

#### INSTRUCTIONS FOR USE AND MAINTENANCE

#### GENERAL INFORMATION

If the chair is used as a computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

#### GAS PUMP

Instructions for use: The height adjustment of the seat by gas pump is obtained by pulling the lever of the mechanism upwards.

Maintenance instructions: the pump does not require any particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant. Warnings: Do not open the gas column by force. Specialized staff only can replace or repair the gas pump.

#### **MECHANISMS**

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to prevent it from returning abruptly and accidentally forward.

Care instructions: It is recommended to clean the mechanism periodically to prevent dust or other indoor pollutants from affecting its operation or causing squeaking.

Warnings: All mechanism adjustments (height, sideshift, seat and backrest adjustment, swivel) must be operated while seated to avoid improperly straining the mechanism. When adjusting, be careful to avoid any risk of entrapment or crushing of the fingers.

#### PADDED PARTS

#### Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

#### UNPADDED PARTS

#### Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

#### PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water: For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.

#### CASTORS

Tips: When using the chair on tiled floors, carpets or rugs, we recommend the use of polyamide castors. For stone, wood, laminate floors, we recommend the use of soft desmopan rubber castors. Maintenance and cleaning instructions: It is advisable to clean the castors periodically to avoid the accumulation of dirt that can cause malfunction. Warnings: Do not stress the sliding of the castors on floors with pronounced joints as the difference in height can cause them to break.

### In. Fb. Ig.