

# **LUNA**

# **CHAIRS AND TUB CHAIRS**

Design: R&D Sitlosophy®





The top model features a generously thick seat, supported by 4 wooden feet, which enhances its comfort and sturdiness. The versatility of LUNA makes it perfect for a variety of public areas, such as hotels, waiting rooms, meeting rooms and bars, transforming any environment into a welcoming and stylish place. With a range of bright colours for coverings, LUNA is the ideal choice for those who want to create unique and captivating spaces.



## **Specifications**

Structure	Heat-bent multilayer
Padding	Flexible polyurethane foam 5 - 2 cm thick, density 35 rc
Armrests	Heat-bent multilayer
Swivel base	B70 4-star black aluminum on item 1680; 4-spokes black nylon pyramid on items 1682/1683 B68; 4-star polished aluminum on item 1681; 4-spokes polished aluminum pyramid on item 1684
Fixed base	4-legged natural varnished beechwood on item 1685
Feet	Natural varnished beechwood on item 1686



## Components and/or modules

Image	Dimension		Cod.	Description	
	Н	81			
	L	62	N1680B	Swivel armchair, 4-star black painted aluminum base	
	Р	70			
	Н	84		Swivel armchair, black 4-spokes pyramid nylon base	
	L	62	N1682B		
_	Р	67	_		
	Н	84			
	L	62	N1683B	Swivel armchair, black 4-spokes pyramid nylon base on castors	
	Р	67			
	Н	81		Swivel armchair, 4-star polished aluminum base	
	L	62	C1681B		
	Р	70			
	Н	83			
	L	62	- C1684B -	Swivel armchair, 4-spokes pyramid polished aluminum base	
	Р	72			
	Н	84			
	L	62	W-N1685V	Armchair, 4-legged natural varnished beechwood legs	
	Р	66			
	Н	77			
	L	62	W-N1686V	Armchair, natural varnished beechwood feet	
1	Р	63			



## Coverings


Cat.	Covering		Description	Certifications	Folder Colors
2		Angel 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 1IM	Ø
2		One 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	OEKO-TEX © STANDARD 100 POSSIS CONTROOT Total parameters of the control parameters of the contro	Ø
2		<b>Gazebo</b> 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 1IM	Ø.
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	Trevira  STANDARD 100  OPANA COMMON TRANSPORTED TO THE STANDARD TO THE STANDAR	Ø,
3		Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 1IM	Ø
3		Mini 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	OEKO-TEX®  STANDARD 100  PORT OF THE PROPERTY	Ø
3		Chili 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	OEKO-TEX ⊕  STANDARD 100 €  STANDARD 100 €  Distillation relief.  STANDARD 100 €  STANDARD 10	Ø
4		Leather 13 colors	100% genuine leather	Vera pelle	Ø
5		Step 15 colors	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	CEKO-TEX® STANDARD 100 Parties Common and the commo	Ø

3



Cat.	Covering		Description	Certifications	Folder Colors
5		Go Check 15 colors	Weight: ± 310 g/sqm Composition: 100% Trevira CS Martindale: 80,000 cycles	OEKO-TEX © STANDARD 100 © STANDARD 1	0
6		Panama leather 15 colors	Composition: 100% corrected grain leather Thickness: 1.0 – 1.2 mm Flexural strength: 50,000 cycles	Vera pelle Flame resistance treatment available on request	90
7		Grain 15 colors	Weight: ± 615 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles California TB 117-2013	OEKO-TEX® CONFIDENCE IN TEXTLES STANDARD 100 1076-1807 Tested for harmful substances, www.peip-tex.com/standard100	90
7		Focus 15 colors	Weight: ± 660 g/sqm Composition: 100% New Zealand Wool Martindale: 100,000 cycles CLASS 1 IM - UNI 9175	OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 1076-182 DT Tested for harmfal substances, www.oeko-tex.com/standard100	9
7		Extrema 15 colors	Weight: ± 480 g/sqm Composition: 63% PU – 29% COT – 8% PES Martindale: 150,000 cycles Features: Antibacterial protection	Ultra-Fresh*	S

## **Finishes**



Polished aluminum Black aluminum Beech wood

## Certifications















Ministerial Homologation Class 1IM on request. Search for FSC® products



https://www.sitlosophy.com/en/seat/luna/



### **INSTRUCTIONS FOR USE AND MAINTENANCE**

#### **GENERAL INFORMATION**

If the chair is used as a computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately  $90^\circ$ 

#### **MECHANISMS**

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to prevent it from returning abruptly and accidentally forward.

Care instructions: It is recommended to clean the mechanism periodically to prevent dust or other indoor pollutants from affecting its operation or causing squeaking.

Warnings: All mechanism adjustments (height, sideshift, seat and backrest adjustment, swivel) must be operated while seated to avoid improperly straining the mechanism. When adjusting, be careful to avoid any risk of entrapment or crushing of the fingers.

#### **PADDED PARTS**

Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

#### **UNPADDED PARTS**

Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo color alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces

PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water; For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.

#### CASTORS

Tips: When using the chair on tiled floors, carpets or rugs, we recommend the use of polyamide castors. For stone, wood, laminate floors, we recommend the use of soft desmopan rubber castors. Maintenance and cleaning instructions: It is advisable to clean the castors periodically to avoid the accumulation of dirt that can cause malfunction. Warnings: Do not stress the sliding of the castors on floors with pronounced joints as the difference in height can cause them to break