

# **MIRAI WHITE**

TASK CHAIRS Design: R&D Sitlosophy®



Mirai is a classic task chair that comes from the union between a soft seat, ideal for prolonged use, and the traditional polypropylene back. It is completed with different mechanisms, from the up-down movement of the backrest to the synchronized adjustment with seat slider. The use of a light plastic makes the armchair current and contemporary, suitable even for the most informal work contexts. It is available in three sizes, the largest of which, combined with the headrest, makes it a semi-executive armchair.

#### Specifications

Seat	Multilayer	
Backrest	Reinforced polypropylene	
Headrest	Reinforced polypropylene, reclining and height-adjustable	
Outer shell	White polypropylene	
Padding	Polyurethane foam 5/4 cm thick, density 35/30 rc	
Armrests	3D in polypropylene,height-adjustable with rotating and sliding black PU pad or Height-adjustable in black or white polypropylene	
Mechanism	MEC 8A Self adjusting synchro with shock proof system. MEC 9 Multi block synchro with shock proof system, side control lever, seat slider on TR version. Height-adjustable backrest by up-down action	90 90
Height adjustment	Gas pump (UNI 9084 certified)	
Castors	AR8 ø50 Polyamide	
Swivel base	B69 white nylon	

In. Fb. lg.



#### Components and/or modules

Image	Dimension		Cod.	Description	
2	Н	118-127	B530D	<b>-</b>	
	L	50		Task armchair, maxi backrest with up-down system, height adjustable headrest, self- adjusting multiblock synchro mechanism, white base and outer shell	
	Р	70			
-	Н	118-127		Task armchair,maxi backrest with updown system, height adjustable headrest,multi block synchro mechanism, seat slider, white	
	L	50	B530DTR		
enteres.	Р	70		base and outer shell	
	Н	110-119			
	L	50	B531D	Task armchair,maxi backrest with up-down system, self-adjusting multiblock synchro mechanism, white base and outer shell	
	Р	70			
	Н	110-119	B531DTR		
	L	50		Task armchair,maxi backrest with up-down system, multi block synchro mechanism, seat slider, white base and outer shell	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Р	70			
	Н	98-107	B532D		
-	L	50		Task armchair,up-down backrest, self-adjusting multi block synchro mechanism, white base and outer shell	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Р	70		monument, mile base and outer shell	
	Н	98-107	B532DTR	Task armchair,up-down backrest, multi block synchro mechanism, seat slider, white base and outer shell	
-	L	50			
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Р	70			



Image	Dimension	Cod.	Description
ŢĴ		BRB3/S	Pair of height-adjustable armrests in white polypropylene
ŢĴ		BRB4/S	Pair of white polypropylene 3D armrests with sliding and rotating grey PU pad
33		GS4	Pair of black polypropylene brackets with knob for width adjustment of BR 4



#### Coverings

Cat.	Covering		Description	Certifications	Folder Colors
1		Madrid 5 colors	Weight: ± 230 g/sqmComposition: 100% PP polypropylene F.R.Martindale: 80,000 cycles	EKO-TEX® STANARD 100 Microsoft Contractor Mark Printer and Stand Fire proof class 11M	Ø
1		<b>Cove</b> 5 colors	Weight: ± 565 g/sqm Composition: 82% PVC – 7% Cotton – 11% Polyester Martindale: 50,000 cycles		Ø
2		Angel 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 1IM	Ø
2		<b>One</b> 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	DEKO-TEX © STADACTICO USUS CONTROL Mages balan want Mages balan want Mages balan want Fire proof class 1IM	Ø
2		<b>Gazebo</b> 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 11M	Ø
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	CERCO-TEX® STANDARD TOO OF STANDARD TO	Ø
3		Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 11M	Ø
3		<b>Mini</b> 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	CEKO-TEX STANDARD 100 (Standard and A	Ø
3		<b>Chili</b> 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	CEKO-TEX® STANDARD 93316 CONTROL Watch Bandwardth Window Mathematich Troiseose Fire proof class 1IM	Ŷ

### In. Fb. Ig.



Cat.	Covering		Description	Certifications	Folder Colors
5		<b>Step</b> 15 colors	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	VEKO-TEX® STANDARD 100 Para Common Main Hand Stand Common Main Hand Stand Common Main Hand Stand Common Main Hand Stand Stand Para Hand St	Q
5		<b>Go Check</b> 15 colors	Weight: ± 310 g/sqm Composition: 100% Trevira CS Martindale: 80,000 cycles	OEKO-TEXO Instantion Image: Constant of the second of the se	Q
7		<b>Grain</b> 15 colors	Weight: ± 615 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles California TB 117-2013	OEKO-TEX ® CONTIDENCE IN TEXTILES STANDARD 100 1076-182 0T Tatad for harmful subdators, www.color-tac.com/standard.100	Q
7		Focus 15 colors	Weight: ± 660 g/sqm Composition: 100% New Zealand Wool Martindale: 100,000 cycles CLASS 1 IM - UNI 9175	CONTIDENCE IN TEXTUS CONTIDENCE IN TEXTUS STANDARD 100 U70-182 0TI Tested for humid subtranse, www.osko-tex.com/standard.100	Q
7		Extrema 15 colors	Weight: ± 480 g/sqm Composition: 63% PU – 29% COT – 8% PES Martindale: 150,000 cycles Features: Antibacterial protection	Ultra-Fresh*	Ø



### In. Fb. Ig.

## SIT LOSOPHY®

#### INSTRUCTIONS FOR USE AND MAINTENANCE

#### GENERAL INFORMATION

If the chair is used as a Computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

#### GAS PUMP

Instructions for use: The height adjustment of the seat by gas pump is obtained by pulling the lever of the mechanism upwards.

Maintenance instructions: the pump does not require any particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant. Warnings: Do not open the gas column by force. Specialized staff only can replace or repair the gas pump.

#### **MECHANISMS**

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to prevent it from returning abruptly and accidentally forward.

Care instructions: It is recommended to clean the mechanism periodically to prevent dust or other indoor pollutants from affecting its operation or causing squeaking.

Warnings: All mechanism adjustments (height, side shift, seat and backrest adjustment, swivel) must be operated while seated to avoid improperly straining the mechanism. When adjusting, be careful to avoid any risk of entrapment or crushing of the fingers.

#### PADDED PARTS

#### Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

#### UNPADDED PARTS

#### Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

#### PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water: For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.

#### CASTORS

Tips: When using the chair on tiled floors, carpets or rugs, we recommend the use of polyamide castors. For stone, wood, laminate floors, we recommend the use of soft desmopan rubber castors. Maintenance and cleaning instructions: It is advisable to clean the castors periodically to avoid the accumulation of dirt that can cause malfunction. Warnings: Do not stress the sliding of the castors on floors with pronounced joints as the difference in height can cause them to break.

### In. Fb. Ig.