

# **UPPER**

# **STOOLS**

Design: Nicola Cacco Design



Upper is a collection of stools for counters and high tables. The version with padded seat and painted metal structure, perfectly matching the tables in the same finishes, is ideal for more dynamic environments. The more classic variants, also with backrest, are either completely upholstered or entirely in wood. In both cases, the structure can be equipped with four legs or height-adjustable.

## **Specifications**

Seat	Pressed Multilayer Beechwood, natural finish on version W-F
Padding	flexible polyurethane foam 2 cm thick, density 40 rc
Structure	Steel tube ø60x1,5 Chrome or painted in: corten, yellow, white, charcoal
Height adjustment	Chrome gas pump (UNI 9084 certified)
Swivel base	Slip-proof, inox steel pedestal base ø410 Chrome or painted in: corten, yellow, white, charcoal
Fixed base	4-Legs chrome steel tube ø16x2on item C3



# Components and/or modules

Image	Dimension		Cod.	Description
	Н	75-100		
	L	40	C1G	Swivel padded stool, chrome frame
*	Р	41	_	
	Н	74-99		
	L	38	C1 G W-F	Swivel stool, beechwood shell, chrome frame
	Р	41		
<u>_</u>	Н	75-100	_	
	L	40	C2G	Swivel padded stool, chrome frame
	Р	41		
	Н	74-100	_	
0	L	38	C2 G W-F	Swivel stool, beechwood shell, chrome frame
	Р	41		
	Н	96	_	
	L	46	C3V	Padded stool, 4-legged chrome base
	Р	51		
	H	95	_	
	L	46	C3 V W-F	Beechwood stool, 4-legged chrome base
	Р	51		
7	H	55-80	_	
+	L	43	MR4G	Swivel stool, upholstered seat, gas lift, corten painted structure
	Р	41		



Image	age Dimension		Cod.	Description
7	Н	55-80		Swivel stool, upholstered seat, gas lift, yellow painted frame
+	L	43	GL4 G	
	P	41		
T	Н	55-80	- B4 G -	Swivel stool, upholstered seat, gas lift, white painted structure
+	L	43		
	Р	41		
7	Н	55-80	AT4 G	
+	L	43		Swivel stool, upholstered seat, gas lift, charcoal painted frame
	P	41		










# **Metal finishes**





# Coverings

Cat.	Covering		Description	Certifications	Folder Colors
1		<b>Madrid</b> 5 colors	Weight: ± 230 g/sqmComposition: 100% PP polypropylene F.R.Martindale: 80,000 cycles	OEKO-TEX® CONTROLL OF TENED STANDARD 100 MOROODE CONTROLL STANDARD 100 MORODE CONTROLL STANDARD 100 MOROODE CONTROLL STANDARD 100 MOROODE CONTROLL STANDARD 100 MOROODE CONTROLL STANDARD 100 MOROODE CONTROLL STANDARD 100 MORODE CONTROLL STA	0
1		Cove 5 colors	Weight: ± 565 g/sqm Composition: 82% PVC – 7% Cotton – 11% Polyester Martindale: 50,000 cycles		90
2		Angel 13 colors	Weight: ± 228 g/sqm Composition: 100% polypropylene F.R. Martindale: 100,000 cycles	Fire proof class 1IM	0
2		One 15 colors	Weight: ± 350 g/sqm Composition: 100% recycled polyester Martindale: 100,000 cycles	OEKO-TEX © STANDARD 100  CT313 CONTROOT Tendage souther value, reasoners factorized to the control of the contr	0
2		<b>Gazebo</b> 15 colours	Weight: ± 640 g/sqm Composition: 87.5% Plasticized Polyvinyl Chloride – 4.4% Cotton- 8.1% Polyester Martindale: 50,000 cycles	Fire proof class 1IM	0
2		King-flex 15 colours	Weight: ± 300 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	Treviral Standard Tool Standar	0
3		Secret 15 colors	Weight: ± 540 g/sqm Composition: 76% PVC – 2% PU – 22% PES Martindale: 60,000 cycles Features: waterproof, UV-resistant, suitable for outdoor	Fire proof class 1IM	9
3		Mini 15 colors	Weight: ± 340 g/sqm Composition: 100% polyester Trevira CS Martindale: 100,000 cycles	Trevira  OEKO-TEX®  STANDARD 100  POR STANDARD 1	6
3		Chili 15 colors	Weight: ± 470 g/sqm Composition: 100% Post-consumer recycled polyester FR Martindale: 60,000	CEKO-TEX © CEMPORATI TO USE TO STANDARD 100	6



Cat.	Covering		Description	Certifications	Folder Colors
5	的现在分词 1995年 19	tep 5 colors	Weight: ± 340 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles	OEKO-TEX®  STANDARD 100  Princip Control  Princip Control	Ø6
5		o Check 5 colors	Weight: ± 310 g/sqm Composition: 100% Trevira CS Martindale: 80,000 cycles	STANDARD 100 STAND	Ø.
7		i <b>rain</b> 5 colors	Weight: ± 615 g/sqm Composition: 100% Trevira CS Martindale: 100,000 cycles California TB 117-2013	OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 1076-182 DT Tested for harmful substances, www.zele-ta.com/standard100	Op.
7		ocus 5 colors	Weight: ± 660 g/sqm Composition: 100% New Zealand Wool Martindale: 100,000 cycles CLASS 1 IM - UNI 9175	OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 Tode-182 DIT Tested for harmful substances, www.oeko-tax.com/standard100	O6
7	TO THE RESIDENCE OF THE PROPERTY OF THE PERSON OF THE PERS	xtrema 5 colors	Weight: ± 480 g/sqm Composition: 63% PU – 29% COT – 8% PES Martindale: 150,000 cycles Features: Antibacterial protection	Ultra-Fresh* Fire proof class 11M	90

## Certifications

















Ministerial Homologation Class 1IM on request. Search for FSC® products



https://www.sitlosophy.com/en/seat/upper/



#### INSTRUCTIONS FOR USE AND MAINTENANCE

#### **GENERAL INFORMATION**

If the chair is used as a Computer station, the angles between the foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

#### **GAS PUMP**

Instructions for use: The height adjustment of the seat by gas pump is obtained by pulling the lever of the mechanism upwards.

Maintenance instructions: the pump does not require any particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant. Warnings: Do not open the gas column by force. Specialized staff only can replace or repair the gas pump.

#### **MECHANISMS**

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to prevent it from returning abruptly and accidentally forward.

Care instructions: It is recommended to clean the mechanism periodically to prevent dust or other indoor pollutants from affecting its operation or causing squeaking.

Warnings: All mechanism adjustments (height, side shift, seat and backrest adjustment, swivel) must be operated while seated to avoid improperly straining the mechanism. When adjusting, be careful to avoid any risk of entrapment or crushing of the fingers.

#### **PADDED PARTS**

Care instructions:

Leatherette: Clean with a damp cloth, mild soap and rinse well with water. It is imperative to avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, light-coloured materials cannot be put in contact with clothes containing unfixed dyes (e.g. jeans and derivatives) in order to avoid stains or streaks that are difficult to remove

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would change the fire behaviour of the fabric. Gently dab from the edges to the centre of the stain, do not rub. After stain removal, it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth dampened with water and neutral soap by making regular circular movements. Dry gently after treatment. Gently dab from the edges to the centre of the stain, do not rub. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner regularly with a smooth nozzle, without brushing or scrubbing in any way. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some upholstery (leather, imitation leather, weft fabrics) may have a slightly different aesthetic result depending on the batch, the dyeing bath and the product to be made. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change appearance and texture over time, this is to be considered normal.

#### **UNPADDED PARTS**

Care instructions:

Mesh: Use the vacuum cleaner regularly with a smooth spout, without brushing or scrubbing in any way. Any stains can be removed using a cloth dampened with water and neutral soap with regular circular movements. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any dust residue or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powder cleaners that may damage the paintwork. avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wooden surfaces, being a natural material themselves, may undergo colour alterations with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a damp and soft cloth soaked in water, it is not recommended to use dry cloths that could load with rubbing

electrostatically the plastic surface by attracting dust. For more stubborn stains, neutral liquid soap can be diluted in water in moderation. The use of solvents, bleaches or other chemical detergents should be strictly avoided, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive

substances such as washing powders, abrasive pastes, scouring pads or rough sponges. Avoid dragging objects that can scratch the material on surfaces.

# PAINTED / CHROME-PLATED METAL BASES AND STRUCTURES

Maintenance and cleaning instructions: Both steel or aluminum metal surfaces and painted surfaces should be cleaned with a damp, soft cloth soaked in warm water; For more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois skin. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and scouring pads that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as but not limited to muriatic acid, ammonia, rubbing alcohol, bleach, sulphuric acid, soda, etc.